

MOQUETTE



TECHNICAL DETAILS

MANUFACTURING PROCESS	DIN ISO 2424	TUFTED 1/10"
FRONTSIDE STRUCTURE	DIN ISO 2424	CUT PILE - SAXONY
COLOR	DIN ISO 2424	CHROMOJET PRINT
PILE MATERIAL		100 % POLYAMID PA 6
PRIMARY BACKING	DIN ISO 2424	PES WOVEN
SECONDARY BACKING	DIN ISO 2424	ACTION BACK
PILE WEIGHT	DIN ISO 2424	Approx. 1050 g/m ²
TOTAL WEIGHT	ISO 8543	Approx. 2222 g/m ²
PILE HEIGHT	ISO 1766	Approx. 5,5 mm
TOTAL THICKNESS	ISO 1765	Approx. 6,8 mm
NUMBER OF KNOTS	ISO 1763	Approx. 213000/m ²
WIDTH	DIN 3018	Approx. 400 cm

FUNCTIONAL PROPERTIES

WEAR CLASSIFICATION	EN 1307:2019	23/32
COMFORT RATING	EN 1307:2019	LC 3
CASTOR CHAIR RESTISTANCE	EN 985:Prüfung A	CLASS A

PHYSICAL PROPERTIES

FIRE RATING	DIN EN 13501-1	Cfl-s1
glued on massive mineral concrete		

FASTNESSES

COLOUR FASTNESS TO LIGHT	EN ISO 105-B02:2013	6-7
COLOUR FASTNESS TO WATER	DIN EN ISO 105 E01:2013	5
RUBBERING FASTNESS DRY/WET	DIN EN ISO 105 X12:2002	5/5



! ALL ARTICLES CAN BE PRINTED WITH ALL THE GRAPHICS' COLLECTION.

