

MOQUETTE

CARPETS



MATERIALE PREGIATO DAL PELO CORTO E CONFORTEVOLE, LA MOQUETTE È IL COMPLEMENTO D'ARREDO IN CUI I MOTIVI, GLI SCENARI E LE SFUMATURE DELLE GRAFICHE INSTABILELAB SI ESPRIMONO NELLO SPAZIO CON CARATTERE E MASSIMA LIBERTÀ DI PERSONALIZZAZIONE. È QUESTA LIBERTÀ CHE LO RENDONO UN ELEMENTO DI UNICITÀ NEL MONDO DELL'HÔTELLERIE, MA ANCHE UNA SCELTA AUDACE E DECISIVA NELLE ABITAZIONI CHE ACQUISISCONO UN FASCINO INTIMO E SENZA TEMPO.

NELLA QUALITÀ PREGIATA DI QUESTO MATERIALE RAFFINATO AL TATTO E ALLA VISTA RISIEDA LA POSSIBILITÀ DI UNA RESA IMPECCABILE DI QUALSIASI DESIGN SCELTO. FONOASSORBENTE E FACILE DA PULIRE, LA MOQUETTE INSTABILELAB CONFERISCE CALORE A OGNI ATMOSFERA ADATTANDOSI E TRASFORMANDO QUALSIASI SPAZIO. UN COMPLEMENTO CAPACE DI FARE LA DIFFERENZA TRA UN AMBIENTE IMPECCABILE E UNO MEMORABILE.

TECHNICAL DETAILS

MANUFACTURING PROCESS	DIN ISO 2424	TUFTED 1/10"
FRONTSIDE STRUCTURE	DIN ISO 2424	CUT PILE - SAXONY
COLOR	DIN ISO 2424	CHROMOJET PRINT
PILE MATERIAL		100 % POLYAMID PA 6 - ECONYL
PRIMARY BACKING	DIN ISO 2424	PP/PA WOVEN
SECONDARY BACKING	DIN ISO 2424	ACTION BACK
PILE WEIGHT	DIN ISO 2424	Approx. 1200 g/m ²
TOTAL WEIGHT	ISO 8543	Approx. 2300 g/m ²
PILE HEIGHT	ISO 1766	Approx. 6,0 mm
TOTAL THICKNESS	ISO 1765	Approx. 8,0 mm
NUMBER OF KNOTS	ISO 1763	Approx. 213000/m ²
WIDTH	DIN 3018	Approx. 400 cm

FUNCTIONAL PROPERTIES

WEAR CLASSIFICATION	EN1307:2014+A3:2018	33
COMFORT RATING	EN1307:2014+A3:2018	LC 5
CASTOR CHAIR RESTISTANCE	EN 985:Prüfung A	CLASS A

PHYSICAL PROPERTIES

FIRE RATING	DIN EN 13501-1	Cfl-s1 *1
-------------	----------------	-----------

*glued on massive mineral concrete


FASTNESSES

COLOR FASTNESS TO LIGHT	EN ISO 105-B02:2013	7
-------------------------	---------------------	---

SUSTAINABILITY

EMISSIONS	TÜV PROFICERT PREMIUM	Nr. 707107640-1
-----------	-----------------------	-----------------

FONDO MOQUETTE



Fondo strutturato moquette.



FOR AREAS WITH
NORMAL COMMERCIAL USE



FLAME RETARDANT C_{fl}-s1



PERMANENT USE



LUXURY CLASS LC 5



CE MARKING

ECONYL

