

MOQUETTE

CARPETS



A FINE MATERIAL WITH A SHORT AND COMFORTABLE PILE, WALL-TO-WALL CARPET IS THE FURNISHING ACCESSORY IN WHICH THE PATTERNS, SCENARIOS AND NUANCES OF INSTABILELAB GRAPHICS ARE EXPRESSED IN SPACE WITH CHARACTER AND MAXIMUM FREEDOM OF CUSTOMISATION. IT IS THIS FREEDOM THAT MAKES IT A UNIQUE ELEMENT IN THE WORLD OF HÔTELLERIE, BUT ALSO A BOLD AND DECISIVE CHOICE IN HOMES THAT ACQUIRE AN INTIMATE AND TIMELESS CHARM.

IN THE FINE QUALITY OF THIS MATERIAL REFINED TO THE TOUCH AND TO THE EYE LIES THE POSSIBILITY OF AN IMPECCABLE RENDERING OF ANY CHOSEN DESIGN.

SOUND-ABSORBING AND EASY TO CLEAN, INSTABILELAB WALL-TO-WALL CARPETING ADDS WARMTH TO ANY ATMOSPHERE, ADAPTING TO AND TRANSFORMING ANY SPACE. A COMPLEMENT CAPABLE OF MAKING THE DIFFERENCE BETWEEN AN IMPECCABLE ENVIRONMENT AND AN UNFORGETTABLE ONE.

TECHNICAL DETAILS

MANUFACTURING PROCESS	DIN ISO 2424	TUFTED 1/10"
FRONTSIDE STRUCTURE	DIN ISO 2424	CUT PILE - SAXONY
COLOR	DIN ISO 2424	CHROMOJET PRINT
PILE MATERIAL		100 % POLYAMID PA 6 - ECONYL
PRIMARY BACKING	DIN ISO 2424	PP/PA WOVEN
SECONDARY BACKING	DIN ISO 2424	ACTION BACK
PILE WEIGHT	DIN ISO 2424	Approx. 1200 g/m ²
TOTAL WEIGHT	ISO 8543	Approx. 2300 g/m ²
PILE HEIGHT	ISO 1766	Approx. 6,0 mm
TOTAL THICKNESS	ISO 1765	Approx. 8,0 mm
NUMBER OF KNOTS	ISO 1763	Approx. 213000/m ²
WIDTH	DIN 3018	Approx. 400 cm

FUNCTIONAL PROPERTIES

WEAR CLASSIFICATION	EN1307:2014+A3:2018	33
COMFORT RATING	EN1307:2014+A3:2018	LC 5
CASTOR CHAIR RESTISTANCE	EN 985:Prüfung A	CLASS A

PHYSICAL PROPERTIES

FIRE RATING	DIN EN 13501-1	Cfl-s1 *1
-------------	----------------	-----------

*glued on massive mineral concrete


FASTNESSES

COLOR FASTNESS TO LIGHT	EN ISO 105-B02:2013	7
-------------------------	---------------------	---

SUSTAINABILITY

EMISSIONS	TÜV PROFICERT PREMIUM	Nr. 707107640-1
-----------	-----------------------	-----------------

MOQUETTE BACKING



Moquette structured backing.



FOR AREAS WITH NORMAL COMMERCIAL USE



FLAME RETARDANT C_{fl}-s1



PERMANENT USE



LUXURY CLASS LC 5



CE MARKING

ECONYL

